

FIK-RPU Remote Paging Unit

The FIK-RPU is a remote paging unit that provides a supervised microphone, eight emergency message buttons, and sixteen mappable audio switches. This lower profile remote paging unit is ideal for locations where the standard LOC will not fit.

The FIK-RA2000 and FIK-RA100 have the same height and flush mount depth as the FIK-RPU, so if your installation requires a fully functioning LOC with annunciation, the FIK-RA2000 or FIK-RA100 can be installed right next to the FIK-RPU for a sleek installation.



COMPATIBILITY

The FIK-RPU is compatible with the following Fike FCP series FACP's:

- FCP-300ECS
- FCP-2100ECS
- FIK-RA100 (used with FCP-300ECS)
- FIK-RA2000 (used with FCP-2100ECS)

FEATURES

- Smaller footprint than the ECS-RCU
- Supervised microphone
- Connects to control panel via 4-wire SBUS and 2-wire VBUS
- Eight emergency communication button messages
- Sixteen mappable audio switches
- Surface or flush mounted
- Opens 180 degrees for easy access to the board
- Complies with NFPA 70 and NFPA 72: Central Station; Remote Signaling; Local Protective Signaling Systems; Auxiliary Protected Premises Unit and Water Deluge Releasing Service

APPROVALS

- UL Listed
- Factory Mutual Approved
- CSFM

For exact certification listings, please reference the respective agency website.

SPECIFICATIONS

Physical	
Mounting Dimensions:	Flush Mount: 16.375"W x 10"H (41.6 cm W x 25.4 cm H)
Overall Dimensions:	17.739"W x 11.372"H x 3.329"D (45.057 cm W x 28.885 cm H x 8.456 cm D)
Color:	Red
Environmental	
Operating Temperature:	32°F - 120°F (0°C - 49°C)
Humidity:	10% - 93% non-condensing
Electrical	
Standby Current:	70 mA
Alarm Current:	100 mA

ORDERING INFORMATION

Part Number	Description
FIK-RPU	Remote Paging Unit
Accessories	
THUMBLTCH	Turn latch lock