

FIK-PULL-SA and FIK-PULL-DA

Intelligent Pull Stations

The FIK-PULL-SA is a single-action pull station requiring only one action to activate the station. The FIK-PULL-DA is a dual-action pull station requiring two actions to activate the station. Both pull stations can be used with Fike's FCP Series fire alarm control panels (FACP).

The FIK-PULL-SA and FIK-PULL-DA are extremely easy to operate and provide a fast and practical means of manually initiating a fire alarm signal. The FACP recognizes each pull station by its specific address, saving precious seconds in determining an alarm's location.

The FIK-PULL-SA and FIK-PULL-DA can be surface mounted to an SB-I/O surface back box or semi-flush mounted on a standard single-gang, double-gang, or 4" (10.61 cm) square electrical box with a minimum depth of 2.13" (5.4 cm). An optional trim ring (BG-TR) is available if the station is being semi-flush mounted.


COMPATIBILITY

The FIK-PULL-SA and FIK-PULL-DA are compatible with the following Fike FCP series panels:


- FCP-75
- FCP-300 / FCP-300ECS
- FCP-2100 / FCP-2100ECS
- RFCP-2100

FEATURES

- Installer can open the station without causing an alarm condition
- Dual-color LED is visible through the handle of the station, blinks green to indicate normal operation, and remains steady red in an alarm condition
- Key operated test and reset lock using lock plate actuator
- Key matches compatible FACP locks
- Meets ADA requirements for 5 lbs. maximum pull force to activate
- Meets the Americans with Disabilities Act Accessibility Guidelines (ADAAG)
- Reliable analog communications for trouble-free operation
- Braille text on station handle
- Rotary address switches for fast installation
- Handle latches in the down position, and the word "Activated" appears, clearly indicating the station has been pulled



FIK-SA



FIK-DA

APPROVALS

- UL Listed (UL 38)
- CSFM
- Factory Mutual Approved

For exact certification listings, please reference the respective agency website.

SPECIFICATIONS

| | |
|-------------------------------|--|
| Dimensions (HxWxD): | 5.5" x 4" x 1.45" (14 x 10.2 x 3.7 cm) |
| Housing Material: | LEXAN® polycarbonate resin |
| Bi-Colored LED: | Blinking Green: Normal Steady Red: Alarm |
| Switch: | Single pole, single-throw (SPST) normally open (N/O) switch closes upon activation of the pull station |
| Operating Temperature: | 32°F to 120°F (0°C to 49°C) |
| Humidity: | 10 to 93%, non-condensing |
| Operating Voltage: | 15 – 32 Vdc |
| SLC Current: | 350 μ A max. @ 24 Vdc (standby and alarm) |
| Wire Gauge: | Up to 12AWG (3.1 mm ²) |

ORDERING INFORMATION

| Part Number | Description |
|--------------------|---------------------------------|
| FIK-PULL-SA | Single Action Pull Station |
| FIK-PULL-DA | Dual Action Pull Station |
| Accessories | |
| BG-TR | Optional Trim Ring |
| SB-I/O | Surface backbox, indoor/outdoor |