


## RELAY MODULE



### Features

- Provides four additional, independently programmable Single Pole, Double Throw (SPDT) relays.
- Compatible with CyberCat®, Cheetah® Xi, or SHP PRO® Control Panels\*.
- Can support up to two CRM4 modules on the main controller board.
- Can be wired across normally open or normally closed contacts.
- Interfaces to the main control board using four standoffs supplied with the CRM4.

*\*Not compatible with the CyberCat 50 and Cheetah Xi 50 control systems.*

### Approvals

Underwriters Laboratories (UL)  
 Factory Mutual (FM)  
 California State Fire Marshal (CSFM)  
 City of New York  
 City of Denver  
 City of Chicago

*For exact certification listings, please reference the respective agency web site.*


## Specifications

Current Consumption	11mA (normal standby) 39 mA (alarm), all relays active.
P42 Terminal (Relays 1-4)	SPDT Form C relay contact C = Common NO = Normally Open NC = Normally Closed
DC Rating	2A @ 30 VDC (pf = .35)
AC Rating	0.5A @ 120 VAC (pf = .35)
Dimensions	3.5" L x 1.5" H x 2" D (8.9cm x 3.8cm x 5.08cm).
Weight	0.10 lbs.
Operating Temperature	32 to 120°F (0°C to 49°C)
Operating Humidity	93% RH, non-condensing.
Compatibility	CRM4 is compatible with Fike's Cheetah, Cheetah Xi, SHP PRO, CyberCat 254 and 1016 fire alarm and suppression panels.

## Ordering Information

Part Number	Description
10-2204	CRM4 Relay Module
02-12031	Standoff hardware kit (includes P/N 02-3794 and 02-1589)
02-3794	Standoff, 1.25" f/f, 6 x 32 hex (qty 4)
02-1589	Screw, 6-32 x 0.375 Philips (qty 8)

## Product Diagram



This document is only intended to be a guideline and is not applicable to all situations. Information is subject to Fike's full disclaimer at <http://www.fike.com/disclaimer>.