

H9650 Linear Heat Detection Cable

240°C, 464°F Nominal



The simple and proven technology of digital Linear Heat Detection (LHD) cable, makes it a product of choice for difficult and challenging applications where other technologies struggle to work.

With its ease of installation and low maintenance it also provides a cost effective solution where project expenditure requires to be kept at a minimum.

The sensing cable is formed from a pair of twisted steel conductors each with temperature sensitive insulation and then an overall Fluoropolymer outer sleeve. When the temperature sensitive insulation reaches its predetermined alarm temperature the two conductors short together providing the digital or switched signal.

The cable can be connected to any unit capable of monitoring a switched signal, i.e. Conventional fire panel, addressable switch monitor unit or PLC.

The Fluoropolymer outer sleeve of the H9650 offers excellent chemical and water resistance, allowing it to be deployed in harsh and dirty environments.

Features

Simple digital switch operation

Continuous sensing along the total length of the element

Fixed alarm temperature. Unaffected by changes in ambient temperature

Compatible with switch monitoring units and conventional alarm panels

Suitable for use in Hazardous areas using safety barriers

Chemical & water resistant
Fluoropolymer outer sleeve

Rugged and durable construction

Simple maintenance free installation.

Small diameter and bend radius

FM Approved

Applications

Conveyors / bearing protection

Escalators, moving walkways

Petro-chemical storage tanks, rim seal protection

Cable tunnel / tray protection

Road and rail tunnels

Road and rail motor compartments

Electrical switch gear & transformers

Refrigerated rooms and cold stores

Building exteriors under eaves

Motor and pump overheat detection

Dirty and dusty environments



H9650 Linear Heat Detection Cable - 240°C, 464°F Nominal

Specifications.

Alarm temperature :	240°C
Max amb temperature :	200°C
Min operating temperature :	-50°C
Min installation temperature :	-20°C

Mechanical

Outside Diameter :	3.5mm
Colour :	White.
Number of cores :	2
Core diameters :	0.9mm
Core colours:	Black and white.
Minimum bend radius :	50mm (Cold store 100mm)
Weight :	24.0Kg/Km on the reel. (weight of reel typically 2Kg)

Electrical

Resistance :	100 ohms / Km @ 20°C
Capacitance :	45 pF to 130 pF
Inductance :	0.74 µH to 1.3 µH
Voltage rating :	110vdc 1amp

Time to detect small flame : 20 sec (Flame touching)

Ordering Information

Part Number

51100-240

Description

H9650 sensing cable 240°C Alarm temperature
White Fluoropolymer outer sleeve. (ordered by the meter)

Optional

52100-001	DLI-2K Digital Location Interface 2Km
52100-002	DLI-10K Digital Location Interface 10Km
52101-001	DIM Digital Interface Module
53000-001	Portable test oven 1m

I