

GOYU.EX4447 Carbon Dioxide Extinguishing System Units, Marine

Page Bottom

Carbon Dioxide Extinguishing System Units, Marine

See General Information for Carbon Dioxide Extinguishing System Units, Marine

FIKE CORP EX4447

704 S 10TH ST PO BOX 610 BLUE SPRINGS, MO 64015 USA

High Pressure Carbon Dioxide Extinguishing System Units in the 50, 75 and 100 lb capacities having an operating pressure of 850 psi at 70 F and an operating temperature range of 0 F to 130 F.

A description of these extinguishing system units and the limitations of the hazards to be protected are contained in the installation manual dated August 2002. Copies of the manual are available from the above Listee.

Last Updated on 2003-02-25

Questions? Notice of Disclaimer Page Top

Copyright © 2007 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2007 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

