



### CO, MARINE INSTRUCTIONAL SIGNS

#### **APPLICATION**

Instructional signs are provided to inform personnel of any potential hazards they face when operating certain devices or working within areas protected by CO<sub>2</sub> systems. All signs are made of stainless steel and have black lettering as shown.

#### **DESCRIPTION**

This warning sign must be located next to each Pneumatic Actuator Assembly in accordance with CFR Title 46, Section 95.15-10(h).

#### **SPECIFICATIONS**

Part Number: C02-1367

Size: 10" x 14" x .025"

(254 mm x 356 mm x .6 mm)

Material: 304 Stainless Steel

## WARNING

OPERATION OF THIS PRIMARY ACTUATION DEVICE FOLLOWED BY OPERATION OF THE SECONDARY ACTUATION DEVICE WILL CAUSE CARBON DIOXIDE TO DISCHARGE.

BEFORE OPERATING, BE SURE PERSONNEL ARE CLEAR OF THE DISCHARGE AREA.

#### **DESCRIPTION**

This warning sign must be located next to the Latch Door Pull Box that operates the Stop Valve in accordance with CFR Title 46, Section 95.15-10(h).

#### **SPECIFICATIONS**

Part Number: C02-1368

Size: 10" x 14" x .025"

(254 mm x 356 mm x .6 mm)

Material: 304 Stainless Steel

# WARNING

OPERATION OF THIS SECONDARY ACTUATION DEVICE MUST BE PRECEDED BY OPERATION OF THE PRIMARY ACTUATION DEVICE TO CAUSE CARBON DIOXIDE TO DISCHARGE

BEFORE OPERATING, BE SURE PERSONNEL ARE CLEAR OF THE DISCHARGE AREA.

#### **DESCRIPTION**

This sign must be located next to the Local Lever Actuators, (or Pull Boxes that operate the Actuators), in accordance with CFR Title 46, Section 95.15-10(h).

#### **SPECIFICATIONS**

Part Number: C02-1388

Size: 10" x 14" x .025"

(254 mm x 356 mm x .6 mm)

Material: 304 Stainless Steel



ACTUATION OF THIS DEVICE WILL CAUSE CARBON DIOXIDE TO DISCHARGE.

BEFORE ACTUATING, BE SURE ALL PERSONNEL ARE CLEAR OF THE AREA.

002-1388 NC

Form No. E.1.26.01-1

#### **DESCRIPTION**

This warning sign should be located in any nearby space where CO<sub>2</sub> may accumulate after discharge.

#### **SPECIFICATIONS**

Part Number: C02-1390

Size: 10" x 14" x .025"

(254 mm x 356 mm x .6 mm)

304 Stainless Steel Material:

WHEN ALARM OPERATES VACATE AREA IMMEDIATELY.

A CARBON DIOXIDE DISCHARGE IN A NEARBY SPACE MAY CONCENTRATE IN THIS AREA.

#### **DESCRIPTION**

This warning sign should be located throughout the protected space in accordance with CFR Title 46, Section 95.15-10(h).

#### **SPECIFICATIONS**

Part Number: C02-1391

10" x 14" x .025" Size:

(254 mm x 356 mm x .6 mm)

304 Stainless Steel Material:



WHEN ALARM OPERATES VACATE IMMEDIATELY.

**AREA PROTECTED BY CARBON DIOXIDE GAS EXTINGUISHING SYSTEM.** 

#### **DESCRIPTION**

This warning sign must be located at all entrances to the protected space in accordance with CFR Title 46, Section 95.15-10(h).

#### **SPECIFICATIONS**

Part Number: C02-1392

10" x 14" x .025" Size:

(254 mm x 356 mm x .6 mm)

Material: 304 Stainless Steel



WHEN ALARM OPERATES DO NOT **ENTER AREA UNTIL IT HAS** BEEN VENTILATED.

**CARBON DIOXIDE GAS MAY** OCCUPY AREA.

### **DESCRIPTION**

This warning sign is used to inform all persons entering the protected area that a CO<sub>2</sub> system is in place and that they should not enter the area if the CO<sub>2</sub> system has been activated until it is safe to do so. This sign should be posted at all entrances to the protected area.

#### **SPECIFICATIONS**

Part Number: 02-1398

14" wide x 10" high Size:

(35.6 cm x 25.4 cm)



Carbon dioxide gas can cause injury or death. When alarm operates. do not enter until ventilated



Copyright © Fike Corporation All Rights Reserved.

Form No. E.1.26.01-1 January, 2008 Specifications are subject to change without notice.