

IR3-H2-HD TRIPLE IR HYDROGEN FLAME DETECTOR



Ordering

FIK-IR3-H2-HD-AS11 ¹	Detector, HD video output, M25 conduit openings
FIK-IR3-H2-HD-AS21 ¹	Detector, HD video output, ¾" NPT conduit openings
FIK-TMO-S02 ²	Tilt Mount, Stainless Steel (shown above)
FIK-TMA-S01 ^{2,3}	Adapter, Universal Overhead Mount
FIK-USB/RS485 ^{2,4}	RS-485 to USB Converter Kit
FIK-Weather Cover ^{2,5}	Weather Cover, Stainless Steel

¹ Where ATEX approval is required, contact Fike at 1-800-979-3453 (option 2,1) for ordering information.

² Ordered separately

³ Used for mounting a detector to other manufacturers mounting bracket. Installs on top of the detector.

⁴ Converts detector RS-485 communication network to USB for connection to a computer port.

⁵ Used only in very hot or very cold environments.

Introduction

The IR3-H2-HD flame detector provides ultra-fast response, high performance and reliable detection of hydrogen (H₂) fires. The detector addresses slow growing fires as well as fast eruptions of fire using improved IR3 technology. The detector operates in all weather and light conditions.

In addition, the detector provides high-definition (HD) video output of the monitored area with clear imaging of a fire event and of personnel at distances up to 100 ft. (30m). This allows the rescue team to be aware of the exact situation before entering the hazardous area. The detector automatically records video of fire event (1 minute pre- and up to 3 minutes post-alarm initiation). These features, along with the built-in event logger, provide additional means to study the cause and development of fire events.

Key Benefits

- High immunity to false alarm
- Ultra-fast detection mode detection within 40 milliseconds for Hydrogen fireballs or explosions
- Hydrogen flame detection
- High sensitivity – up to 100 ft. (30m)
- HD video output with Automatic HD video recording of fire events
- Data/Event logger – alarms, faults and other relevant events are logged to non-volatile memory
- Ethernet communication – in addition to the standard methods, such as 4-20mA and Modbus
- Built-in-Test (BIT) – Automatic and manual internal self-test of window cleanliness and the overall operation of the detector
- Window heater to avoid condensation and icing
- Tilt mounting bracket can be connected either above or below the detector.

This document is only intended to be a guideline and is not applicable to all situations. Information is subject to Fike's full disclaimer at <http://www.fike.com/disclaimer>.

Immunity to False Alarm

False Alarm Source	Modulated		Unmodulated	
	Distance ft. (m)	Response	Distance ft. (m)	Response
Sunlight, Direct, Reflected		No Alarm		No Alarm
Incandescent frosted glass light, 300W	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Fluorescent, 70W (3x23.3W)	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Electric arc	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Arc welding	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Radiation heater, 18502000W	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Quartz lamp (1000W) shielded	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Quartz lamp (500W) non-shielded	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Mercury vapor lamp 160Wx3	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Exhausts	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Projector LED	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Solenoid bell	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Soldering iron	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Electric Drill	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm

Response Characteristics

Fuel	Size	Sensitivity	Distance ft. (m)	Average Response Time (Sec)
H ₂	32-in Plume	Extreme	98 (30)	4.0
H ₂	32-in Plume	Medium	66 (20)	1.6
H ₂	32-in Plume	Low	33 (10)	1.5
Methanol	1 x 1 ft.	Extreme	59 (18)	4.3
Methanol	1 x 1 ft.	Medium	30 (9)	1.6

This document is only intended to be a guideline and is not applicable to all situations.
Information is subject to Fike's full disclaimer at <http://www.fike.com/disclaimer>.

FIRE DETECTION	Detection time and distance	40ms for fast burst of explosion 1.5s for 32" (0.8m) hydrogen fire at 0-66 ft. (0-20m) 4s for 32" (0.8m) hydrogen fire at 66-100 ft. (20-30m)
	Field of view (IR detection)	90° Horizontal, 75° Vertical
	Time Delay	0-30 seconds (adjustable)
	Built in Test	Automatic or Manual
VIDEO FUNCTIONALITY	HD Video	Allows clear imaging of fire and humans at 100 ft. (30m) distance
	Video recording of alarm events	1-minute pre-event and 3 minutes post-event
	System integration protocol	ONVIF (Open Network Video Interface Forum) Profile S
ELECTRICAL SPECIFICATIONS	Operating Voltage	24 VDC nominal (18-32 VDC)
	Current Consumption	Standby: 180mA Maximum: 250mA all systems in operation (including window heater)
	Conduit Entries	2x conduit entries ¾" 14NPT or M25x1.5
	Wiring	12-20AWG (2.5-0.35mm ²)
OUTPUTS	Relays	Volt-free contacts rated 2A at 30 VDC Alarm – normally open Fault – normally closed
	0-20mA (stepped) current output	3 wire and 4 wire configurations (sink and source)
	Indication	Tri-color LED
	Modbus	RTU compatible on RS-485
	Digital (for video)	IP network IEEE 802.3 10Base-t
	Composite video	NTSC or PAL
	Size	7.87 x 5.12 x 5.12" (200 x 130 x 130 mm)
MECHANICAL SPECIFICATIONS	Weight	Detector (stainless steel 316): 9.8 lbs. (4.4 kg) Tilt mount (stainless steel 316): 5.4 lbs. (2.4 kg)
	Temperature Range	Operating: -67°F to +167°F (-55°C to +75°C) Option: -67°F to +185°F (-55°C to +85°C) Storage: -67°F to +185°F (-55°C to +85°C)
	Humidity	Up to 99% (RH), non-condensing
ENVIRONMENTAL SPECIFICATIONS	Ingress Protection	IP66 & 68; NEMA 4X & 6P
	Explosion proof	ATEX: II 2 G D** Ex db IIC T5 Gb or Ex db eb IIC T5 Gb and Ex tb IIIC T95°C Db -55°C<Ta<75°C Ex db IIC T4 Gb or Ex db eb IIC T4 Gb and Ex tb IIIC T105°C Db -55°C<Ta<85°C FM & FMC Class I, Div. 1, Groups B, C & D: T4 T4 -50°C≤Ta≤85°C T5 -50°C≤Ta≤75°C
	Performance	ANSI FM 3260
APPROVALS*	Functional Safety	Complies to SIL2, per IEC 61508
	DNV GL	Designed to meet standard DNVGL-CG-0339 for open deck locations Temperature Class D; Vibration Class A, B and C
	EAC CU TR	
ACCESSORIES	Weather shield	
	Adapters for connecting different mounts	
WARRANTY	5 Years	

*All products designed and tested to relevant approval standards.

**Where ATEX approval is required, contact Fike at 1-800-979-3453 (option 2,1) for ordering information.

This document is only intended to be a guideline and is not applicable to all situations.
Information is subject to Fike's full disclaimer at <http://www.fike.com/disclaimer>.