

### IR3 FLAME DETECTOR



#### Ordering

FIK-IR3-AS11	Detector with M25 conduit openings
FIK-IR3-AS21	Detector with ¾" NPT conduit openings
FIK-TMO-S01 <sup>1</sup>	Tilt Mount, Stainless Steel (shown above)
FIK-TMA-S01 <sup>1,2</sup>	Adapter, Universal Overhead Mount
FIK-USB/RS485 <sup>1,3</sup>	RS-485 to USB Converter Kit
FIK-Weather Cover <sup>1,4</sup>	Weather Cover, Stainless Steel

<sup>1</sup> Ordered separately.

<sup>2</sup> Used for mounting a detector to other manufacturers mounting bracket. Installs on top of the detector.

<sup>3</sup> Converts detector RS-485 communication network to USB for connection to a computer port.

<sup>4</sup> Used only in very hot or very cold environments.

#### Introduction

The IR3 flame detector provides ultra-fast response, high performance and reliable detection of all types of hydrocarbon fires (visible and non-visible). The detector addresses slow growing fires as well as fast eruption of fire using improved triple IR (IR3) technology. It operates in all weather and light conditions with highest immunity to false alarms.

- Detection within 40 milliseconds of fireballs or explosions
- Standard fire in only 1.3 seconds from 50 ft. (15m) and 3.7 seconds from 230 ft. (70m).

Add to that, the integral event recording, on top of the proven superior capabilities of Triple IR (IR3) flame detection and you have a very powerful safety tool to protect your personnel, plant and process.

#### Key Benefits

- High immunity to false alarm
- Extreme sensitivity – up to 260 ft. (80m) for a 1 ft<sup>2</sup> (0.1m<sup>2</sup>) n-heptane pan fire
- Ultra-fast detection mode – detection within 40 milliseconds for fireballs or explosions
- 1.3 seconds detection time – for 1 ft<sup>2</sup> (0.1m<sup>2</sup>) n-heptane pan fire at up to 50 ft. (15m) distance
- Data/Event logger – alarms, faults and other relevant events are logged to non-volatile memory
- Built-in-Test (BIT) – Automatic and manual self-test of window cleanliness and the overall operation of the detector
- Window heater to avoid condensation and icing
- Tilt mounting bracket can be connected either above or below the detector.

This document is only intended to be a guideline and is not applicable to all situations. Information is subject to Fike's full disclaimer at <http://www.fike.com/disclaimer>.

## Immunity to False Alarm

False Alarm Source	Modulated		Unmodulated	
	Distance ft. (m)	Response	Distance ft. (m)	Response
Sunlight, Direct, Reflected		No Alarm		No Alarm
Incandescent frosted glass light, 300W	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Fluorescent, 70W (3x23.3W)	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Electric arc	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Arc welding	20.0 (6.0)	No Alarm	20.0 (6.0)	No Alarm
Radiation heater, 1850W	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Quartz lamp (1000W) shielded	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Quartz lamp (500W) non-shielded	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Mercury vapor lamp 160Wx3	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Car Exhausts	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Projector LED	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Solenoid bell	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Soldering iron	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Electric Drill	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm

## Response Characteristics

Fuel	Size	Sensitivity	Distance ft. (m)	Average Response Time (s)
N-Heptane	1 x 1 ft.	Extreme	262 (80)	7.1
N-Heptane	1 x 1 ft.	Extreme	230 (70)	3.7
N-Heptane	1 x 1 ft.	High	197 (60)	2.7
N-Heptane	1 x 1 ft.	Medium	98 (30)	2.6
N-Heptane	1 x 1 ft.	Low	49 (15)	1.3
Gasoline	2 x 2 ft.	Extreme	328 (100)	5.3
Gasoline	1 x 1 ft.	Extreme	230 (70)	2.8
Gasoline	1 x 1 ft.	Medium	98 (30)	1.5
Methane	32-in Plume	Extreme	148 (45)	2.6
Methane	32-in Plume	Medium	82 (25)	0.6
LPG	32-in Plume	Extreme	180 (55)	3.7
LPG	32-in Plume	High	148 (45)	2.6
LPG	32-in Plume	Medium	98 (30)	1.4
LPG	32-in Plume	Low	49 (15)	1.5
Diesel	1 x 1 ft.	Extreme	164 (50)	2.6
Diesel	1 x 1 ft.	Medium	79 (24)	3.2
JP5	2 x 2 ft.	Extreme	295 (90)	9.4
JP5	1 x 1 ft.	Extreme	164 (50)	4.5
JP5	1 x 1 ft.	High	148 (45)	4.4
JP5	1 x 1 ft.	Medium	79 (24)	1.8
JP5	1 x 1 ft.	Low	39 (12)	10.1
Kerosene	1 x 1 ft.	Extreme	164 (50)	3.6
Kerosene	1 x 1 ft.	Medium	79 (24)	2.7
Methanol	1 x 1 ft.	Extreme	131 (40)	4.6
Methanol	1 x 1 ft.	High	125 (38)	4.2
Methanol	1 x 1 ft.	Medium	75 (23)	1.5
Methanol	1 x 1 ft.	Low	39 (12)	1.3
Ethanol	1 x 1 ft.	Extreme	125 (38)	4.7
Isopropanol	1 x 1 ft.	Extreme	180 (55)	3.6
Isopropanol	1 x 1 ft.	Medium	75 (23)	1.8
Polypropylene	1 x 1 ft.	Extreme	115 (35)	7.8
Polypropylene	1 x 1 ft.	Medium	66 (20)	2.1
Paper	1 x 1 ft.	Extreme	79 (24)	1.1
Paper	1 x 1 ft.	Medium	39 (12)	1.1

This document is only intended to be a guideline and is not applicable to all situations.  
Information is subject to Fike's full disclaimer at <http://www.fike.com/disclaimer>.

FIRE DETECTION	<b>Detection time and distance</b>	40ms for fast burst of explosion 2.6s for 1 ft <sup>2</sup> (0.1m <sup>2</sup> ) pan fire at 0-100 ft. (0-30m) 3.7s for 1 ft <sup>2</sup> (0.1m <sup>2</sup> ) pan fire at 100-230 ft. (30-70m)
	<b>Field of view (IR detection)</b>	90° Horizontal, 75° Vertical
	<b>Time Delay</b>	0-30 seconds (adjustable)
	<b>Built in Test</b>	Automatic or Manual
ELECTRICAL SPECIFICATIONS	<b>Operating Voltage</b>	24 VDC nominal (18-32 VDC)
	<b>Current Consumption</b>	Standby: 120mA 180mA all systems in operation (including window heater)
	<b>Conduit Entries</b>	2X conduit entries ¾" 14NPT or M25x1.5
	<b>Wiring</b>	12-20AWG (2.5-0.35mm <sup>2</sup> )
OUTPUTS	<b>Relays</b>	Volt-free contacts rated 2A at 30 VDC Alarm – normally open Fault – normally closed
	<b>0-20mA (stepped) current output</b>	3 wire and 4 wire configurations (sink and source)
	<b>Indication</b>	Tri-color LED
	<b>Modbus</b>	RTU compatible on RS-485
MECHANICAL SPECIFICATIONS	<b>Size</b>	5.51 x 3.54 x 3.54" (140 x 90 x 90 mm)
	<b>Weight</b>	Detector (stainless steel 316): 6.6 lbs. (3.0 kg) Tilt mount (stainless steel 316): 3.3 lbs. (1.5 kg)
ENVIRONMENTAL SPECIFICATIONS	<b>Temperature Range</b>	Operating: -67°F to +167°F (-55°C to +75°C) Option: -67°F to +185°F (-55°C to +85°C) Storage: -67°F to +185°F (-55°C to +85°C)
	<b>Humidity</b>	Up to 99% (RH), non-condensing
	<b>Ingress Protection</b>	IP66 & 68 (2m, 24hr); NEMA 4X & 6P
APPROVALS*	<b>Explosion proof</b>	IECEX Ex db IIC T5 Gb -50°C≤Ta≤75°C Ex db IIC T4 Gb -50°C≤Ta≤85°C  FM & FMC Class I, Div. 1, Groups B, C & D: T4 Class I, Zone 1, AEx/Ex db IIC T4 Gb T4 -50°C≤Ta≤85°C T5 -50°C≤Ta≤75°C
	<b>Performance</b>	ANSI FM 3260 EN 54-10
ACCESSORIES	<b>Weather shield</b>	
	<b>Adapters</b> for connecting different mounts	
WARRANTY	<b>5 Years</b>	

\*All products designed and tested to relevant approval standards. Where ATEX approval is required, contact Fike at 1-800-979-3453 for ordering information.

This document is only intended to be a guideline and is not applicable to all situations.  
Information is subject to Fike's full disclaimer at <http://www.fike.com/disclaimer>.