

## **DECLARATION OF PERFORMANCE**

ACCORDING TO CONSTRUCTION PRODUCTS REGULATION EU N° 305/2011

## **DOP 323-0001**

1.	. Unique Product identification code:					
	Sita Hipoint with Short Circuit Isolator	323-0001				
2.	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):					
323-0001						
3.	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:					
	Fire detection and fire alarm system (For indoor use only).	_				
4.	<ul> <li>Name, registered trade name or registered trad required pursuant to Article 11(5):</li> </ul>	e mark and contact address of the manufacturer as				
	Fike Safety Technology Ltd. Unit 31, Springvale Industrial Estate Cwmbran, Torfaen NP44 5BD, United Kingdom					
5.	Where applicable, name and contact address of the authorised representative whose mandate covers he tasks specified in Article 12(2):					
	Not applicable					
6.	<ul> <li>System or systems of assessment and verification product as set out in Annex V:</li> </ul>	on of constancy of performance of the construction				
	System 1					
7.	<ul> <li>In case of the declaration of performance concessions</li> <li>standard:</li> </ul>	erning a construction product covered by a harmonised				
	BRE Global Ireland – 2831					
	Performed type testing and an inspection of the control under system 1 and issued following cer	e manufacturing plant and of factory production tilicate of constancy of performance:				
2831 – CPR – F4126						
8.	. In case of the declaration of performance conce Technical Assessment has been issued:	erning a construction product for which a European				
	Not applicable, see point 7					





## **DECLARATION OF PERFORMANCE**

ACCORDING TO CONSTRUCTION PRODUCTS REGULATION EU Nº 305/2011

9.Declared Performance					
	Performance	Harmonised technical specification			
Essential characteristics		EN54 – 3: 2001 +A1: 2002 + A2: 2006	EN54 - 17: 2005		
Nominal activation conditions / Sensitivity, Response delay (response time) and Performance under fire conditions	Pass	4.2, 4.3, 5.2, 5.3			
Operational reliability	Pass	4.4, 4.5, 4.6, 5.4	4.2 to 4.9		
Durability of operational reliability and response delay, Temperature resistance	Pass	5.5, 5.7, 5.8, 5.9	5.4, 5.5		
Durability of operational reliability, Vibration resistance	Pass	5.12 to 5.15	5.9 to 5.12		
Durability of operational reliability, Humidity resistance	Pass	5.8, 5.9	5.6, 5.7		
Durability of operational reliability, Corrosion resistance	Pass	5.11	5.8		
Durability of operational reliability, Electrical stability	Pass	5.16	5.3, 5.13		
Performance under fire conditions	Pass		5.2		
Durability of operational reliability: resistance to ingress	Pass	5.17			

10. The performance of the product Identified in points 1 & 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in 4.

Signed for and on behalf of the manufacturer by:

(Name and Function) Mark Kendall – General Manager (Place and date of issue)

(Signature) M. L. Cwmbran 12<sup>th</sup> Feb 20

